




FRAISES

Fraises

Fräser

End mills

Frese

2	2	0	1	4	2	6	00	S	M	220.142.600	220.142.600S	220.142.600M
MD HM/SC MG KX10	Fraises Fräser End mills Frese			Z4 		$\lambda 38^\circ$ $\gamma \sim 5^\circ$		AlTiN	PSNM			



VARIA
cut



gamme élargie

Type NS
Norme OPTI

D _{h10}	d _{h6}	l ₁	L	Z	Non revêtu	Revêtu AlTiN	Revêtu PSNM
1	6	3	50	4	220.142.600-01		220.142.600M-01
1.5	6	4	50	4	220.142.600-01.5		220.142.600M-01.5
2	6	5	50	4	220.142.600-02		220.142.600M-02
2.5	6	6	50	4	220.142.600-02.5		220.142.600M-02.5
3	6	6	50	4	220.142.600-03	220.142.600S-03	220.142.600M-03
3.5 *	6	6	50	4	220.142.600-03.5	220.142.600S-03.5	220.142.600M-03.5
4	6	7	50	4	220.142.600-04	220.142.600S-04	220.142.600M-04
5	6	8	50	4	220.142.600-05	220.142.600S-05	220.142.600M-05
6	6	10	50	4	220.142.600-06	220.142.600S-06	220.142.600M-06
8	8	12	50	4	220.142.600-08	220.142.600S-08	
10	10	14	50	4	220.142.600-10	220.142.600S-10	

* Livrable avec revêtement TiAlN N jusqu'à épuisement du stock

INEO
Tech
>>> p 145