




FRAISES

Fraises

Fräser

End mills

Frese

2	2	0	1	4	5	6	00	S	220.145.600	220.145.600S
MD HM/SC MG KX10	Fraises Fräser End mills Frese			Z4 		$\lambda 38^\circ$ $\gamma \sim 5^\circ$		AlTiN		



VARIA
cut



Type NS
Norme OPTI

D_{h10}	d_{h6}	l_1	L	Z	Non revêtu	Revêtu AlTiN
3	6	10	57	4	220.145.600-03	220.145.600S-03
3.5	6	10	57	4	220.145.600-03.5	220.145.600S-03.5
4	6	12	57	4	220.145.600-04	220.145.600S-04
5	6	14	57	4	220.145.600-05	220.145.600S-05
6	6	16	57	4	220.145.600-06	220.145.600S-06
8	8	22	63	4	220.145.600-08	220.145.600S-08
10	10	24	72	4	220.145.600-10	220.145.600S-10
12	12	28	83	4	220.145.600-12	220.145.600S-12
16	16	35	92	4	220.145.600-16	220.145.600S-16
18	18	35	92	4	220.145.600-18	220.145.600S-18
20	20	40	104	4	220.145.600-20	220.145.600S-20
25	25	50	121	4	220.145.600-25	220.145.600S-25

INEO
Tech
>>> p 145